



◆仕様 (ワンタッチホルダー、電源端子台付ホルダーの場合はご指示下さい)

種別 (W)	電圧 (V)	力率	品番		付属 グロー球	全長 (mm)	取付ピッチ (mm)	全幅W (mm)	全高H (mm)	重量 (kg)	梱包 (本)
			50Hz	60Hz							
52W	100V	低力	INB・S-521A/S	INB・S-521B/S	FG-52P	1685	1604	62	97	1.95	10
40W			INB・S-401A/S	INB・S-401B/S	FG-4P	1235	1154	48	89	1.23	
32W			INB・S-321A/S	INB・S-321B/S	FG-5P	865	784	48	89	1.13	
30W			INB・S-301A/S	INB・S-301B/S	FG-1E	665	584	53	94	0.97	
20W			INB・S-201A/S	INB・S-201B/S	FG-1E	615	534	48	88	0.71	
15W			INB・S-151A/S	INB・S-151B/S	FG-1E	470	389	48	88	0.70	
10W			INB・S-101A/S	INB・S-101B/S	FG-7E	365	284	48	88	0.68	
52W			INB・S-521AC/S	INB・S-521BC/S	FG-52P	1685	1604	62	97	2.07	
40W			INB・S-401AC/S	INB・S-401BC/S	FG-4P	1235	1154	48	89	1.31	
32W			INB・S-321AC/S	INB・S-321BC/S	FG-5P	865	784	48	89	1.21	
30W	200V	高力	INB・S-301AC/S	INB・S-301BC/S	FG-1E	665	584	53	94	1.11	10
20W			INB・S-201AC/S	INB・S-201BC/S	FG-1E	615	534	48	88	0.77	
15W			INB・S-151AC/S	INB・S-151BC/S	FG-1E	470	389	48	88	0.75	
10W			INB・S-101AC/S	INB・S-101BC/S	FG-7E	365	284	48	88	0.73	
52W			INB・S-522A/S	INB・S-522B/S	FG-52P	1685	1604	62	100	1.96	
40W			INB・S-402A/S	INB・S-402B/S	FG-4P	1235	1154	53	94	1.25	
32W			INB・S-322A/S	INB・S-322B/S	FG-4P	865	784	53	94	1.27	
30W			INB・S-302A/S	INB・S-302B/S	FG-4P	665	584	53	94	1.19	
20W			INB・S-202A/S	INB・S-202B/S	FG-4P	615	534	53	94	1.25	
52W			INB・S-522AC/S	INB・S-522BC/S	FG-52P	1685	1604	62	100	2.08	
40W	INB・S-402AC/S	INB・S-402BC/S	FG-4P	1235	1154	53	94	1.27			
32W	INB・S-322AC/S	INB・S-322BC/S	FG-4P	865	784	53	94	1.31			
30W	INB・S-302AC/S	INB・S-302BC/S	FG-4P	665	584	53	94	1.27			
20W	INB・S-202AC/S	INB・S-202BC/S	FG-4P	615	534	53	94	1.23			

※15W・10Wの200Vは特注品です。※52Wホルダーの付属グロー球、FG-52Pは在庫が無くなり次第、順次FE-52Pへ切り替わります。

オプションのご注文の際は

ワンタッチホルダー : 型番の末尾に「J」を付けて下さい  
電源端子台付ホルダー : 型番の末尾に「T」を付けて下さい